



Té de transition 90° - filetage mâle

- Montage sans démontage du raccord
- suitable for PE and PEX pipes
- Eau PN16, DVGW DW-8616CL0433 / VP 609, SSIGE
- Matériel: PP
- Joint: EPDM qualité pour eau potable
- Filetage mâle selon ISO 7/1
- Couleur: bleu/noir

| d | R | PN | Code | SP | GP | poids | D | L | l1 | l2 | l3 | H |
|------|--------|-------|-------------|----|-----|-------|------|------|------|------|------|------|
| (mm) | (inch) | (bar) | | | | (kg) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |
| 20 | ¾ | 16 | 158 400 202 | 10 | 120 | 0,076 | 45 | 134 | 54 | 19 | 14 | 41 |
| 20 | ¾ | 16 | 158 400 203 | 10 | 120 | 0,082 | 45 | 134 | 54 | 19 | 15 | 42 |
| 25 | ½ | 16 | 158 400 204 | 10 | 80 | 0,115 | 53 | 150 | 59 | 21 | 14 | 44 |
| 25 | ¾ | 16 | 158 400 205 | 10 | 80 | 0,118 | 53 | 150 | 59 | 21 | 15 | 46 |
| 25 | 1 | 16 | 158 400 206 | 10 | 80 | 0,123 | 53 | 150 | 59 | 21 | 17 | 48 |
| 32 | ¾ | 16 | 158 400 207 | 10 | 60 | 0,180 | 64 | 173 | 66 | 23 | 15 | 51 |
| 32 | 1 | 16 | 158 400 208 | 10 | 50 | 0,191 | 64 | 173 | 66 | 21 | 17 | 53 |
| 40 | ¾ | 16 | 158 400 209 | 1 | 45 | 0,282 | 75 | 203 | 76 | 26 | 15 | 57 |
| 40 | 1 ¼ | 16 | 158 400 210 | 1 | 30 | 0,298 | 75 | 203 | 76 | 26 | 20 | 62 |
| 40 | 1 ½ | 16 | 158 400 211 | 1 | 30 | 0,304 | 75 | 203 | 76 | 26 | 20 | 62 |
| 50 | ¾ | 16 | 158 400 212 | 1 | 16 | 0,534 | 97 | 239 | 88 | 30 | 15 | 65 |
| 50 | 1 ¼ | 16 | 158 400 213 | 1 | 16 | 0,550 | 97 | 239 | 88 | 30 | 20 | 70 |
| 50 | 1 ½ | 16 | 158 400 214 | 16 | | 0,558 | 97 | 239 | 88 | 30 | 20 | 70 |
| 63 | 1 ¼ | 16 | 158 400 215 | 1 | 8 | 0,978 | 114 | 288 | 104 | 35 | 20 | 81 |
| 63 | 1 ½ | 16 | 158 400 216 | 1 | 8 | 0,982 | 114 | 288 | 104 | 35 | 20 | 81 |
| 63 | 2 | 16 | 158 400 217 | 1 | 8 | 0,985 | 114 | 288 | 104 | 35 | 24 | 85 |
| 63 | 2 ½ | 16 | 158 400 218 | 1 | 8 | 1,024 | 114 | 288 | 104 | 35 | 28 | 89 |
| 75 | 2 ½ | 16 | 158 400 219 | 1 | 7 | 1,630 | 135 | 360 | 133 | 41 | 28 | 101 |
| 75 | 3 | 16 | 158 400 220 | 1 | 6 | 1,674 | 135 | 360 | 133 | 41 | 30 | 104 |
| 90 | 3 | 16 | 158 400 221 | 1 | 2 | 2,697 | 161 | 413 | 150 | 44 | 30 | 116 |
| 110 | 4 | 16 | 158 400 222 | 1 | 2 | 4,072 | 185 | 484 | 175 | 53 | 36 | 138 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>